

NANOCOM - TD5ENG.APP - TD5 ENGINE input file

Engine Spe	Road Speed	Idle Speed	Accel. Way	Accel. Way	Accel. Way	Accel. Supp	Battery (V)	Air Flow (g)
2569	0	1663	1.577	3.506	2.227	5	14.26	277.6
2566	0	1656	1.577	3.506	2.232	5	14.22	281.6
2607	0	1690	1.594	3.489	2.296	5	14.26	285.3
2595	0	1685	1.589	3.493	2.276	5	14.29	279.2
2591	0	1681	1.589	3.5	2.273	5	14.13	280.6
2584	0	1670	1.589	3.493	2.276	5	14.22	281.6
2594	0	1683	1.589	3.489	2.286	5	14.26	280.6
2596	0	1681	1.589	3.493	2.286	5	14.26	281.6
2592	0	1687	1.589	3.493	2.286	5	14.19	284.2
2598	0	1691	1.589	3.493	2.288	5	14.32	283.7
2601	0	1697	1.589	3.489	2.293	5	14.26	282.8
2595	0	1684	1.594	3.489	2.296	5	14.26	283.8
2606	0	1700	1.594	3.489	2.296	5	14.22	282
2613	0	1697	1.594	3.489	2.296	5	14.32	288.7
2611	0	1700	1.594	3.489	2.296	5	14.19	284.2
2604	0	1698	1.594	3.489	2.299	5	14.29	278.1
2618	0	1709	1.594	3.489	2.303	5	14.32	288.3
2618	0	1706	1.594	3.489	2.303	5	14.32	284.2
2609	0	1707	1.594	3.489	2.303	5	14.26	281.7
2613	0	1714	1.594	3.489	2.303	5	14.22	285.2
2606	0	1700	1.594	3.489	2.303	5	14.07	288.7
2617	0	1707	1.594	3.489	2.309	5.005	14.32	286.5
2616	0	1709	1.594	3.489	2.305	5	14.29	287.5
2621	0	1704	1.594	3.489	2.301	5	14.29	287.5
2614	0	1705	1.589	3.489	2.295	5	14.35	286.6
2615	0	1698	1.589	3.489	2.295	5	14.29	284.2
2604	0	1698	1.594	3.489	2.299	5	14.29	287.8
2623	0	1702	1.589	3.489	2.296	5	14.29	283
2610	0	1702	1.594	3.489	2.296	5	14.32	285.3
2606	0	1703	1.589	3.489	2.295	5	14.35	285.3
2620	0	1706	1.589	3.489	2.301	5	14.32	287.8
2623	0	1713	1.589	3.489	2.301	5	14.32	287.8
2622	0	1701	1.594	3.489	2.305	5	14.29	285.3

Ambient Pr	Manifold Turt	Air Inlet Te	Coolant Te	Fuel Temp.	EGR Inlet (%)	EGR Modul	Wastegate	Cylinder 1
101.58	127.81	25.2	77.9	64.6	0	0	0	-1
101.48	128.11	25.2	77.9	64.6	0	0	0	-2
101.37	128.11	25.2	77.9	64.6	0	0	0	-1
101.58	127.83	25.5	77.9	64.6	0	0	0	-1
101.37	127.83	25.5	78.1	64.6	0	0	0	0
101.69	128.99	25.6	78.1	64.6	0	0	0	-3
101.48	128.69	25.7	78.4	64.9	0	0	0	-1
101.48	129.27	25.8	78.5	65	0	0	0	1
101.48	129	26	78.5	64.9	0	0	0	0
101.58	128.99	26.1	78.6	65	0	0	0	-1
101.37	128.99	26.2	78.6	65	0	0	0	-2
101.48	129.27	26.2	78.8	65	0	0	0	-1
101.48	128.41	26.3	78.9	65	0	0	0	1
101.48	129.27	26.3	78.9	65	0	0	0	-3
101.48	129	26.6	79	65	0	0	0	-2
101.58	129	26.6	79.1	65.3	0	0	0	0
101.37	129.57	26.7	79.3	65.3	0	0	0	-2
101.37	129.57	26.7	79.3	65.3	0	0	0	-1
101.48	129.28	26.7	79.5	65.4	0	0	0	-1
101.37	129	26.8	79.5	65.4	0	0	0	0
101.48	129.27	27	79.8	65.5	0	0	0	-2
101.48	129.27	27	79.8	65.5	0	0	0	-1
101.37	129	27.1	79.8	65.5	0	0	0	-1
101.48	129.28	27.2	80	65.5	0	0	0	-1
101.48	129.86	27.2	80	65.5	0	0	0	-1
101.48	129.57	27.2	80.3	65.5	0	0	0	-1
101.58	129.86	27.2	80.4	65.5	0	0	0	-2
101.48	129.86	27.3	80.5	65.8	0	0	0	-1
101.48	129.86	27.5	80.5	65.9	0	0	0	-2
101.48	129.86	27.5	80.5	65.9	0	0	0	-1
101.48	130.14	27.5	80.9	66	0	0	0	-1
101.48	129.86	27.5	80.9	66	0	0	0	-1
101.37	129.86	27.6	80.9	66	0	0	0	-2

Cylinder 2 Cylinder 3 Cylinder 4 Cylinder 5

-5	8	-6	5
-6	9	-5	5
-3	5	-6	5
-6	7	-7	7
-5	6	-6	5
-3	7	-5	2
-6	7	-5	5
-5	5	-4	4
-4	6	-8	6
-6	6	-3	4
-4	6	-4	4
-3	6	-6	3
-6	7	-4	3
-1	6	-5	2
-6	5	-6	7
-6	8	-6	4
-3	6	-4	2
-2	6	-4	1
-3	7	-6	3
-7	6	-6	5
-5	5	-2	4
-2	6	-3	3
-7	5	-5	4
-4	8	-3	2
-3	7	-4	2
-4	6	-5	4
-5	6	-6	6
-4	6	-5	3
-5	8	-4	4
-6	8	-7	6
-6	5	-3	3
-5	6	-7	5
-1	5	-6	5