

NANOCOM - TD5ENG.APP - TD5 ENGINE input file

Engine Spe	Road Speed	Idle Speed	Accel. Way	Accel. Way	Accel. Way	Accel. Supp	Battery (V)	Air Flow (g)
760	0	1	0.829	4.231	0	5	14.19	61.4
757	0	5	0.829	4.231	0	5	14.29	61.9
761	0	2	0.835	4.231	0	5	14.29	62.7
761	0	2	0.829	4.231	0	5	14.22	61.5
757	0	5	0.829	4.231	0	5	13.97	61.7
761	0	1	0.829	4.231	0	5	14.26	61.5
761	0	3	0.829	4.231	0	5	14.13	62
765	0	4	0.829	4.231	0	5	13.97	63.2
766	0	2	0.829	4.231	0	5	14.19	63
760	0	3	0.829	4.231	0	5	14.35	62
761	0	3	0.829	4.231	0	5	14.32	62.7
763	0	0	0.829	4.231	0	5	14.13	62.5
764	0	2	0.835	4.231	0	5	14.22	62.5
764	0	-1	0.829	4.231	0	5	14.19	63.4
761	0	0	0.829	4.231	0	5	14.22	62
759	0	4	0.829	4.231	0	5	14.32	62
764	0	2	0.829	4.231	0	5	14.19	61.2
758	0	1	0.829	4.231	0	5	14.29	62.2
764	0	6	0.829	4.231	0	5	14.22	62
762	0	3	0.829	4.231	0	5	14.22	61.7
761	0	2	0.829	4.231	0	5	14.13	61.9
760	0	3	0.829	4.231	0	5	14.19	61.5
759	0	6	0.835	4.231	0	5	14.19	62
763	0	2	0.829	4.231	0	5	14.26	61.2
761	0	2	0.829	4.231	0	5	14.19	61.7
765	0	-1	0.829	4.231	0	5	14.19	61.7
763	0	-2	0.829	4.231	0	5	14.26	62.5
760	0	-1	0.829	4.231	0	5	14.19	62.2
763	0	-1	0.829	4.231	0	5	14.19	62.5
763	0	5	0.829	4.231	0	5	14.26	61.7
764	0	1	0.829	4.231	0	5	14.32	62.2
762	0	3	0.829	4.231	0	5	14.19	61.2

Ambient Pr	Manifold T	Air Inlet Te	Coolant Te	Fuel Temp.	EGR Inlet (%)	EGR Modul	Wastegate	Cylinder 1
102	104.5	25.2	72	60.7	0	0	0	-1
102	104.5	25.2	72	60.7	0	0	0	2
102	104.5	25.2	72	60.7	0	0	0	-3
102	104.77	25.1	72	60.7	0	0	0	-1
102	104.5	25.1	72	60.9	0	0	0	-3
102	104.77	25.1	72	60.9	0	0	0	-1
102	104.48	25.1	72.3	60.9	0	0	0	2
102	104.5	25.1	72.3	60.9	0	0	0	-1
102.09	104.5	25.1	72.3	60.9	0	0	0	-1
102	104.77	25.2	72.3	60.9	0	0	0	3
102.09	104.5	25.2	72.3	60.9	0	0	0	-2
102	104.5	25.2	72.4	60.9	0	0	0	4
102.09	104.5	25.2	72.4	60.9	0	0	0	0
102	104.5	25.2	72.4	60.9	0	0	0	-3
102	104.77	25.2	72.4	60.9	0	0	0	3
102.09	104.5	25.2	72.4	61	0	0	0	-2
102.09	104.5	25.1	72.3	61	0	0	0	2
102	104.5	25.1	72.3	61	0	0	0	2
102.09	104.5	25.1	72.4	61	0	0	0	0
102.09	104.5	25.1	72.4	61	0	0	0	0
102	104.77	25.1	72.5	61	0	0	0	2
102	104.5	25.1	72.5	61	0	0	0	-1
102	104.5	25.1	72.5	61	0	0	0	1
102	104.5	25.1	72.5	61	0	0	0	1
102.09	104.77	25.1	72.5	61	0	0	0	-4
102	104.5	25.1	72.5	61	0	0	0	3
102	104.5	25.1	72.5	61	0	0	0	-1
102	104.77	25.1	72.5	61	0	0	0	-1
102	104.5	25.1	72.5	61	0	0	0	-3
102.09	104.48	25	72.5	61.2	0	0	0	3
102	104.5	25	72.5	61.2	0	0	0	-2
102.09	104.77	25	72.5	61.2	0	0	0	1

Cylinder 2	Cylinder 3	Cylinder 4	Cylinder 5
------------	------------	------------	------------

-1	4	3	1
0	-1	-1	1
1	4	-2	1
1	1	-2	2
0	4	4	-1
0	0	-1	1
0	0	1	-2
1	-2	-2	-2
1	0	1	-1
-1	1	-1	2
2	1	-1	-1
-2	-3	3	-2
1	-2	-2	0
-1	3	0	1
-1	-3	0	2
2	3	-3	1
-2	0	2	-3
0	-1	-3	2
1	-1	2	-4
0	0	-2	2
-2	3	2	-2
2	1	-1	0
-1	-1	3	-2
1	-1	-1	0
-2	4	2	-2
-2	-3	-2	1
0	2	-1	-1
2	-1	-3	3
0	3	2	-3
0	-4	1	3
2	0	-2	-1
-2	-1	2	-1