

SERVICE CHECK LIST - Range Rover 1995-2002 Model Years

| | Mileage '000miles | | | | |
|---|-------------------|----|----|----|----|
| | 6 | 12 | 24 | 36 | 48 |
| 6,000 mile service applicable for diesel models only | | | | | |
| VEHICLE INTERIOR | | | | | |
| Check condition and security of seats, seat belt mountings, seat belt buckles and operation of inertia seat belts | | X | X | X | X |
| Check condition/operation of front/rear/headlamp washers and wiper blades | | X | X | X | X |
| Check operation of handbrake, adjust if required | | X | X | X | X |
| Depressurise electronic air suspension | | | X | | X |
| Renew electronic air suspension compressor intake and exhaust filters | | | X | | X |
| Remove/refit air reservoir drain plug | | | X | | X |
| Repressurise air suspension system | | | X | | X |
| VEHICLE EXTERIOR | | | | | |
| Check/adjust headlamp and auxiliary lamp alignment | | | X | | X |
| Remove road wheels | | X | X | X | X |
| Check tyres for compliance with manufacturer's specification | | X | X | X | X |
| Check tyres visually for cuts, lumps, bulges, uneven tread wear and depth, tyre pressures | | X | X | X | X |
| Inspect brake pads for wear, caliper fixings for correct torque, calipers for leaks, and disks for condition | | X | X | X | X |
| Refit road wheels to original position | | X | X | X | X |
| Check front wheel alignment | | X | X | X | X |
| Lubricate door locks, check straps, bonnet catches and fuel flap | | X | X | X | X |
| UNDER BONNET | | | | | |
| Check cooling, intercooler and heating systems for leaks, hoses for security and condition. Top up as required | | X | X | X | X |
| Renew spark plugs | | | X | | X |
| Renew fuel filter element (Diesel only) (Replace every 18,000 miles) | | | | X | |
| Drain water from fuel filter (Diesel only) | X | X | X | | X |
| Renew air cleaner element and clean drain hole (Diesel only) | | X | X | X | X |
| Renew air cleaner element and clean drain hole (V8 only) | | | X | | X |
| Renew pollen filters | | X | X | X | X |
| Check condition ancillary driving belt(s) (poly V) | | | X | | X |
| Check/top up automatic transmission fluid | X | X | | X | |

X indicates items carried out during a standard service. Due to our policy of continuous improvement, the work undertaken on your vehicle service may be altered without prior notification.

SERVICE CHECK LIST - Range Rover 1995-2002 Model Years

| | Mileage '000miles | | | | |
|---|-------------------|----|----|----|----|
| | 6 | 12 | 24 | 36 | 48 |
| UNDER BONNET (Continued) | | | | | |
| Check/top up fluid in power steering reservoir | X | X | X | X | X |
| Check/top up brake/clutch fluid reservoir | X | X | X | X | X |
| Check/top up windscreen and rear washer reservoir and ensure screen clean additive content is correct | X | X | X | X | X |
| Lubricate accelerator and cruise control linkages | | X | X | X | X |
| Remove battery connections, clean, grease and refit | | | X | | X |
| Visually check intercooler/radiator for external obstructions | | X | X | X | X |
| Flush diesel intercooler element | | | | | X |
| Check condition of steering intermediate shaft | | | X | | X |
| UNDER VEHICLE | | | | | |
| Renew engine oil and filter | X | X | X | X | X |
| Renew gearbox oil | | | X | | X |
| Check/top up gearbox oil | | X | | X | |
| Renew automatic transmission oil and filter | | | X | | X |
| Renew transfer box oil | | | X | | X |
| Check/top up transfer box oil | | X | | X | |
| Renew front and rear axle oil | | | X | | X |
| Check and top up front and rear axle oil | | X | | X | |
| Lubricate propeller shaft universal/sliding joints | | X | X | X | X |
| Renew fuel filter (V8) | | | | | X |
| Check visually heat shield, brake, fuel, clutch pipes/unions for chafing, leaks and corrosion | | X | X | X | X |
| Check exhaust system for leaks, security and damage | | | X | X | X |
| Check for chafing, corrosion and fluid leaks from steering and suspension systems, hydraulic pipes and unions | | X | X | X | X |
| Check/tighten suspension, steering unit and steering rod ball joint fixings, check condition of ball joints and dust covers | | X | X | X | X |
| Check air suspension pipes and springs for security and damage | | X | X | X | X |
| Check shock absorbers/height sensors and harness assembly for leakage and damage | | X | X | X | X |
| Check road wheel speed sensor electrical harness for damage | | X | X | X | X |
| Carry out road or roller test | X | X | X | X | X |
| Endorse service record and report any unusual features of vehicle condition and additional work required | X | X | X | X | X |

X indicates items carried out during a standard service. Due to our policy of continuous improvement, the work undertaken on your vehicle service may be altered without prior notification.