

USED OIL

MATERIAL SAFETY DATA SHEET

IN CASE OF EMERGENCY CALL: 911

SECTION 1:

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: USED OIL

SYNONYMS: Waste oil; used lubricating oil; Oil and water mixture

PRODUCT PART NUMBER(S): Not applicable.

PRODUCT USE: Oil or water mixture for re-refining or reprocessing. If this product is used in combination with other products, refer to the Material Safety Data Sheets for those products.

SECTION 2:

USED OIL COMPOSITION/INFORMATION ON INGREDIENTS

WT% 80 to 100

CAS NO.: 70514-12-4

0 to 20* Water/solids

0 to 10* Hydrocarbon solvents. May include gasoline, diesel fuel, jet fuel, etc.

0 to 1.5* Metals. May include lead, iron, zinc, copper, chromium, arsenic, nickel, and others: each below 1.0 WT%.

0 to 1.0* Polynuclear aromatics. May include naphthalene, fluoranthene, phenanthrene, pyrene, and others: each below 0.3 WT%.

0 to 0.5* Chlorinated solvents.

SECTION 3:

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE: Liquid, black and viscous (thick), petroleum odor.

WARNING!

PHYSICAL HAZARDS: Combustible liquid.

HEALTH HAZARDS: May be harmful if inhaled. May be harmful if absorbed through skin.

May be harmful or fatal if swallowed. May irritate the respiratory tract (nose, throat, and lungs), eyes, and skin. Suspect cancer hazard. Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure. Contains material which can cause birth defects. Contains material which can cause central nervous system damage.

ENVIRONMENTAL HAZARDS: Product may be toxic to fish, plants, wildlife, and/or domestic animals.

POTENTIAL HEALTH EFFECTS: Effects may vary depending on material composition. Typical effects may include:

INHALATION: High concentrations of vapor or mist may be harmful if inhaled. High (BREATHING): concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs). High concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death.

EYES: May cause irritation.

SKIN: May cause irritation. Product may be absorbed through the skin and cause harm as noted under INHALATION (BREATHING).

INGESTION: May be harmful or fatal if swallowed. May cause throat irritation,

SWALLOWING: nausea, vomiting, and central nervous system effects as noted under **INHALATION (BREATHING)**. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONS:

Individuals with pre-existing cardiovascular, liver, kidney, AGGRAVATED BY respiratory tract (nose, throat, and lungs), central nervous

EXPOSURE: system, eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation may cause oil pneumonia, lung tissue inflammation, fibrous tissue formation, and/or toxic effects as noted under

INHALATION (BREATHING). Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

CANCER: This product contains mineral oils, untreated or mildly treated, which can cause cancer. This product may contain hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics which can cause cancer. Risk of cancer depends on duration and level of exposure. For more information, see SECTION 11: CARCINOGENICITY.

POTENTIAL ENVIRONMENTAL EFFECTS: Product may be toxic to fish, plants, wildlife, and/or domestic animals. Also see SECTION 12: ECOLOGICAL INFORMATION.

SECTION 4:**FIRST AID MEASURES**

INHALATION: (BREATHING) Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

EYES: If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

SKIN: Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists.

INGESTION: (SWALLOWING) Do NOT induce vomiting. Immediately get medical attention. Call 911 If spontaneous vomiting occurs, keep head below hips to avoid breathing the product Into the lungs. Never give anything to an unconscious person by mouth.

NOTE TO PHYSICIANS:

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

SECTION 5:

FIRE FIGHTING MEASURES

FLASH POINT: >200°F (93°C) (minimum) Pensky-Martens Closed Cup

FLAMMABLE LIMITS IN AIR: Not available.

AUTOIGNITION

TEMPERATURE: Not available.

HAZARDOUS COMBUSTION Decomposition and combustion materials may be toxic.

PRODUCTS: Burning may produce phosgene gas, nitrogen oxides, carbon monoxide, and unidentified organic compounds.

CONDITIONS OF FLAMMABILITY: Heat, sparks, or flame. Product may burn but does not ignite readily.

EXTINGUISHING MEDIA: Use carbon dioxide, regular foam, dry chemical, water spray, or water fog.

HAZARD IDENTIFICATION: This information is intended solely for the use by individuals trained in this system.

HEALTH HAZARD

(BLUE)
SPECIFIC
HAZARD
(WHITE)

FIRE FIGHTING INSTRUCTIONS: Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

FIRE AND EXPLOSION HAZARDS: Heated containers may rupture. “Empty” containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact. Product may be sensitive to static discharge, which could result in fire or explosion.

1 01

0

**FIRE HAZARD
(RED)
REACTIVITY
(YELLOW)**

SECTION 6:

ACCIDENTAL RELEASE MEASURES Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in

SECTION 7:

HANDLING AND STORAGE

HANDLING: Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, storage tanks, tanker trucks, and rail tank cars should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using this product.

SHIPPING AND STORING: Keep container tightly closed when not in use and during transport. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition.

Empty product containers may retain product residue and can be dangerous. See TRANSPORT INFORMATION for Packing Group information.

SECTION 8:

EXPOSURE CONTROLS/PERSONAL PROTECTION ENGINEERING CONTROLS:

Use general ventilation, process enclosures, local exhaust ventilation, or other engineering controls to control air-borne levels. Where explosive mixtures may be present, equipment safe for such locations should be used.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION:

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

EYE PROTECTION: Wearing chemical goggles is recommended. Contact lens may be worn with eye protection.

SKIN PROTECTION:

Where prolonged or repeated skin contact is likely, wear neoprene, nitrile (4 mil minimum), PVC (polyvinyl chloride), or equivalent protective gloves; wearing natural rubber or equivalent gloves is not recommended. When product is heated and skin contact is likely, wear heat-insulating gloves, boots, and other protective clothing. To avoid prolonged or repeated contact with product where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits, or other protective clothing.

PERSONAL HYGIENE: Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, and/or

protective equipment if they cannot be thoroughly cleaned. Discard leather articles, such as shoes, saturated with the product.

OTHER PROTECTIVE EQUIPMENT: Where spills and splashes are likely, facilities storing or using this product should be equipped with an emergency eyewash and shower, both equipped with Clean water, in the immediate work area.

SECTION 9:

PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE, APPEARANCE, AND ODOR: Liquid, black and viscous (thick), petroleum odor.

ODOR THRESHOLD: Not available.

MOLECULAR WEIGHT: Not applicable.

SPECIFIC GRAVITY: 0.8 to 1.0 at 60°F (15.6°C) (water = 1)

DENSITY: 6.7 to 8.3 LB/US gal (800 to 1000 g/l) (approximately)

VAPOR DENSITY: greater than 1 (air = 1) (based on kerosene)

VAPOR PRESSURE: Not available.

BOILING POINT: Not available.

FREEZING/MELTING POINT: Not available.

pH: Not applicable.

EVAPORATION RATE: less than 1 (butyl acetate = 1)

SOLUBILITY IN WATER: Slight.

FLASH POINT: >200°F (93°C) (minimum) Pensky-Martens Closed Cup

FLAMMABLE LIMITS IN AIR: Not available.

AUTOIGNITION TEMPERATURE: Not available.

SECTION 10:

STABILITY AND REACTIVITY STABILITY:

Stable under normal temperatures and pressures. Avoid heat, sparks, or flame.

INCOMPATIBILITY: Avoid acids, alkalies, oxidizing agents, reducing agents, reactive halogens, or reactive metals.

REACTIVITY: Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.

HAZARDOUS DECOMPOSITION None under normal temperatures and pressures.
Also see **PRODUCTS: SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.**

SECTION 11:

TOXICOLOGICAL INFORMATION SENSITIZATION:

Based on best current information, there may be known human sensitization associated with this product.

MUTAGENICITY: Based on best current information, there may be mutagenicity associated with this product.

CARCINOGENICITY: Mineral oils, untreated or mildly treated are listed by IARC as a known carcinogen. Mineral oils, untreated or mildly treated are classified by NTP as having limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals. There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are listed by OSHA as known carcinogens. There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are listed by IARC as known, probable, or possible carcinogens. There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are classified by NTP as known carcinogens or as having limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals. There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are recognized by ACGIH as confirmed or suspected human carcinogens.

SECTION 12:

ECOLOGICAL INFORMATION

ECOTOXICITY: Not available.

OCTANOL/WATER

PARTITION COEFFICIENT: Not available.

VOLATILE ORGANIC Not available.

COMPOUNDS: As per 40 CFR Part 51.100(s).

SECTION 13:**DISPOSAL CONSIDERATIONS**

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

SECTION 14:**TRANSPORT INFORMATION**

DOT: Not regulated.

TDG: Not regulated.

EMERGENCY RESPONSE

GUIDE NUMBER: Reference North American Emergency Response Guidebook 127

SECTION 15:**REGULATORY INFORMATION**

USA REGULATIONS Based on the ingredient(s) listed in SECTION 2, this product does not

SARA SECTIONS contain any "extremely hazardous substances" listed pursuant to Title III

302 AND 304: of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA SECTIONS 311 AND 312: This product poses the following physical and health hazards as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard

Delayed (Chronic) Health Hazard

SARA SECTION 313: This product may contain "toxic" chemicals subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

CERCLA: This product may contain "hazardous substances" listed pursuant to Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

TSCA: Not available.

CALIFORNIA: This product is not for sale or use in the State of California.

SECTION 16:

OTHER INFORMATION: USED OIL

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate.

However, assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product as supplied to the user.